




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : B65D 83/14, A61M 15/00	A1	(11) International Publication Number: WO 00/59806 (43) International Publication Date: 12 October 2000 (12.10.00)
(21) International Application Number: PCT/GB00/01180 (22) International Filing Date: 28 March 2000 (28.03.00) (30) Priority Data: 9907928.7 7 April 1999 (07.04.99) GB (71) Applicant (for all designated States except US): BESPAC PLC [GB/GB]; Bergen Way, North Lynn Industrial Estate, King's Lynn, Norfolk PE30 2JJ (GB). (72) Inventors; and (75) Inventors/Applicants (for US only): ALLSOP, Paul, Michael [GB/GB]; 6 Tyndale, North Wootton, King's Lynn, Norfolk PE30 3XD (GB). EAMES, Christopher, John [GB/GB]; 28 Saxon Way, Dersingham, King's Lynn, Norfolk PE31 6LY (GB). CLARK, David, John [GB/GB]; 323 Wootton Road, King's Lynn, Norfolk PE30 3AX (GB). (74) Agent: BOULT WADE TENNANT; Verulam Gardens, 70 Gray's Inn Road, London WC1X 8BT (GB).		(81) Designated States: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i>
(54) Title: DISPENSING APPARATUS COMPRISING A DOSAGE COUNTING DEVICE		
(57) Abstract <p>The present invention relates to dispensing apparatus comprising a housing (10) for receiving a pressurised container (15) containing product for dispensation, series of markings (172) indicative of quantities of product in the container, indicator means (160; 200) for indicating one of the markings of the series, and means for effecting relative movement between the indicator means and the series of markings on actuation of the pressurised container, so as to designate a subsequent marking of the series.</p> 		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

DISPENSING APPARATUS COMPRISING A DOSAGE COUNTING DEVICE

5 The present invention relates to improvements in dispensing apparatus and, in particular, to improvements in apparatus providing means for measuring the quantity of product remaining in a pressurised dispensing container.

10 Pressurised dispensing containers are widely used in the pharmaceutical industry for storing medications and other products to be dispensed in aerosol form. Such containers usually contain a propellant, such as HFC 134a, in which the product is suspended or dissolved. Solvents, such as ethanol, may also be
15 present in the formulation. It is known to provide pressurised dispensing apparatus capable of dispensing metered doses of product from the containers upon each actuation of the container valve, for example, metered dose inhalers. The reliability and consistency of the
20 metered dose is especially important where the product comprises or includes a medication. Inconsistent or unreliable dispensation could result in a user of the dispensing apparatus receiving too great or too little medication.

25 A problem found by many users of such apparatus is the inability to determine the quantity of product remaining in the container. Many types of apparatus continue to allow the dispensing of quantities of propellant and/or solvent when the container is nearly
30 empty, even though the dose of product contained in the propellant is below the required level, thereby exacerbating the problem. Thus, users are often unaware that the dispensing apparatus is operating

inadequately. This has potentially dangerous consequences where the product or medication dispensed is required urgently and no time is available to locate a replacement dispenser, such as in the treatment of asthmatic conditions. Sufferers of asthma often carry dispensers with them for extended periods of time, which may only be used on an occasional basis. Therefore, there is a danger that, where the user is unable to determine the contents of the pressurised dispensing container and the device is required in an emergency situation, the contents of the container may be inadequate.

It is an object of the present invention to provide apparatus for quickly and easily determining the quantity of product remaining in a pressurised dispensing container without the need for special testing equipment. Also, to provide apparatus suitable for use with conventional pressurised dispensing containers.

Accordingly, the present invention provides dispensing apparatus comprising a housing for receiving a pressurised container containing product for dispensation, a series of markings indicative of quantities of product in the container, indicator means for indicating one of the markings of the series, and means for effecting relative movement between the indicator means and the series of markings on actuation of the pressurised container so as to designate a subsequent marking of the series.

Embodiments of the present invention will now be described, by way of example only, with reference to the following drawings, in which:

Figure 1 is a side elevation of a first embodiment of dispensing apparatus according to the present invention;

Figure 2 is a rear elevation of a second embodiment of dispensing apparatus according to the present invention;

Figure 3 is a sectional side elevation of the apparatus of Figure 1;

Figure 4 is a perspective view of an inner housing of the apparatus of Figure 1 containing a dispensing device;

Figure 5 is a schematic diagram of lugs of the apparatus of Figure 1;

Figure 6 is a perspective view of a collar of the apparatus of Figure 1;

Figure 7 is a plan view of a ring of the apparatus of Figure 1;

Figure 8 is a perspective view of a cap of the apparatus of Figure 1;

Figure 9 is a plan view of another version of ring;

Figure 10 is a side elevation of the cap shown in Figure 8 assembled with a dispensing device;

Figure 11 is a schematic view of a part of the outer housing of the apparatus of Figure 1;

Figure 12 is a schematic cross-sectional view of the outer housing of the apparatus of Figure 1;

Figure 13 is a side elevation of an alternative apparatus according to the present invention;

Figure 14 is a perspective view of a marker of an alternative apparatus according to the present invention; and

Figure 15 is a side elevation, showing some

hidden detail, of the marker of Figure 14 assembled with the dispensing apparatus of the present invention.

5 Figures 1 to 12 show a dispensing apparatus according to the present invention. The apparatus comprises a housing 10 having a generally cylindrical portion 11, defining a chamber to slidably receive a pressurised dispensing container 15 and a mouthpiece
10 12, which extends laterally from a lower end of the cylindrical portion 11. The mouthpiece 12 may extend at a slight downward angle from the cylindrical portion 11. The pressurised dispensing container 15 comprises a metering valve attached to a can, for
15 storing the product to be dispensed, by means of a ferrule which is placed over a valve stem of the metering valve and crimped to the open mouth of the can. A valve stem 16 extends axially from the metering valve and defines an outlet through which product is
20 dispensed. The valve stem 16 is received in a valve stem receiving block 13 provided at a distal end of the generally cylindrical portion 11 as the dispensing container 15 is inserted therein. The valve stem receiving block 13 comprises a duct and an orifice
25 such that product dispensed through the outlet of the valve stem 16 is directed through the duct and out of the orifice in the direction of the mouthpiece 12 in the form of an aerosol. Optionally the mouthpiece 12 may be covered by a mouthpiece cover when the
30 apparatus is not being used, in order to protect the mouthpiece 12 from dust, dirt or other matter. In addition, the mouthpiece 12 may be detachable from the generally cylindrical portion 11 to allow for washing

and cleaning of the mouthpiece. Preferably, the detachable portion would include the valve stem receiving block 13 which is the component most prone to becoming clogged with deposits from the pressurised dispensing container 15. An internal lip in the generally cylindrical portion 11 may be provided to retain the pressurised dispensing container 15 within the generally cylindrical portion 11 when the mouthpiece 12 is detached.

10 In the apparatus of the present invention the housing 10 is provided with means to indicate to a user of the apparatus the quantity of product in the pressurised dispensing container.

The apparatus comprises an inner cylindrical housing 140 open at both ends as shown in Figure 4. The inner cylindrical housing 140 is provided with a number of inwardly directed ribs which act to reduce the effective diameter of the aperture. The other end 144 is unobstructed, as shown in Figure 4. In use the pressurised dispensing container 15 is located in the inner housing 140 with valve stem 16 protruding through the aperture. The ribs prevent the container 15 from passing through the aperture. The pressurised dispensing container 15 may be inserted and removed from the inner housing 140, during assembly of the apparatus, through the aperture 144.

The inner housing 140 is provided with an annular flange 142. The flange 142 has a number of protrusions 143 equidistantly spaced around its circumference. An exterior surface of the inner housing 140 has a helical groove 141 extending from the large open end 144 to the flange 142.

Around the inner housing 140 is located a ring

160. As shown in Figure 7, the ring 160 has two pins 161 located on opposite sides thereof. The pins 161 penetrate the ring 160 or are two part elements having an outer portion 164 on an outer surface of the ring 160 and an inner portion 162 on an inner surface of the ring 160. The ring 160 is located around the inner housing 140 such that the inner portion 162 of each pin 161 is received in the groove 141 of the inner housing 140. The ring 160 is thus rotatable about and slidable along the inner housing 140 with the pins 161 constrained to move along helical groove 141. The ring 160 may, in addition, have an arcuate member 163 joined at each end to the outer portions 164 of each pin 161 as shown in Figures 2 and 9.

15 The cylindrical portion 11 of the housing 10 is provided with one or two longitudinally orientated slots 170, as shown in Figure 1. The slots 170 may extend upwardly to contact the open end of the cylindrical portion 11 of housing 10 as shown in Figure 12. The slots 170 may be provided with inserts 173 at their lower ends as shown in Figure 11 to limit the degree to which the pins 161 may move down the slots 170. In this way the number of potential doses dispensed by the apparatus may be reduced so as to ensure that the apparatus is disposed of before there is any danger of reduction in the quantity of product dispensed in each dose. Alternatively the actuator may be moulded with a slot 170 of shorter length so as to reduce the number of potentially deliverable doses.

30 The housing 10 further comprises a collar 155, shown in Figure 6, having a plurality of inwardly directed lugs 156. The lugs 156 have angled upper and lower surfaces, shown schematically in Figure 5. An

outer surface of the collar 155 comprises a notch 157. The internal diameter of the collar 155 is marginally greater than the external diameter of the flange 142 of the inner housing 140. The collar 155 is inserted
5 in housing 10 near a lower end of cylindrical housing portion 11. Notch 157 engages a detent (not shown) on the cylindrical housing portion 11 to prevent rotational movement of the collar 155. Alternatively, collar 155 may be integrally moulded with the
10 generally cylindrical portion 11. As an alternative the protrusions 143 may be provided as inwardly directed protrusions on the collar 155 and the lugs 156 may be provided as outwardly directed lugs on the flange 142.

15 The inner housing 140 is assembled with the main housing 10 such that the valve stem 16 of the pressurised dispensing container 15, which protrudes through the aperture of the inner housing 140 provided with the ribs, is received in the valve stem block 13,
20 as shown in Figure 3. A spring is provided between the inner housing 140 and the main housing 10 to bias the inner housing 140 upwardly away from the valve stem block 13. This may be achieved by means of a compression spring extending between the flange 142,
25 or other part of inner housing 140, and a lower part of the housing 10 or by a tensile spring extending between the flange 142 and an upper part of the housing 10. Alternatively, the internal spring force of the metering valve of the pressurised dispensing
30 container 15, which is used to bias the pressurised dispensing container 15, could be used to bias the inner housing 140 away from the valve stem receiving block 13.

- 8 -

The flange 142 is received in collar 155 with the flange protrusions 143 adjacent to, or contacting the inwardly directed collar lugs 156. The outer portions 164 of pins 161 of ring 160 are located in the slots 170 in the main housing 10 as shown in Figure 1. In the embodiment provided with the arcuate member 163 attached to the ring 160, the arcuate member 163 is positioned around an exterior of the main housing 10 as shown in Figure 2.

A cap 150 as shown in Figures 8 and 10 may be fitted over the open end of the housing 10 on the cylindrical portion 11 to retain the container 15, inner housing 140 and other components in position. The cap 150 comprises two flexible legs 151 which extend downwardly from cap 150 within the housing 10. The legs 151 flex apart as a pressurised dispensing container 15 is inserted through cap 150 into the inner housing 140. As the distal end of the legs pass over the ferrule of the pressurised dispensing container 15 they flex inwardly, thereby trapping the container 15 and preventing its withdrawal.

A push-button cap (not shown) may be provided as part of the main housing 10 to cover the upper portion of the pressurised dispensing container 15. Advantageously, this prevents the ingress of dust, contaminants and moisture into the apparatus.

Markings 172 are printed or embossed on an exterior surface of the housing 10 adjacent the slots 170. The markings 172 may comprise numbers indicating the quantity of product in the pressurised dispensing container 15 in terms of the number of dosages remaining. Alternatively they may comprise a series of descriptive statements indicating how full the

- 9 -

pressurised dispensing container 15 is, such as "FULL", "3/4 FULL", "½ FULL" etc.

Depression of the pressurised dispensing container 15 results in downward movement of the container 15 relative to the housing 10. As the container 15 moves downwardly, the inner housing 140 is caused to move downwardly such that the protrusions 143 contact the angled surfaces of the inwardly directed lugs 156 of collar 155. As a result the inner housing 140 is urged to incrementally rotate about its longitudinal axis. Since pins 161 are received in the slots 170 the ring 160 is incrementally moved vertically relative to the inner housing 140. As a result, the outer portions 164 of pins 160 and/or the arcuate member 163 are moved into alignment with a subsequent marking 172 indicating that the pressurised dispensing container 15 contains one less dose. The angled surfaces of the inwardly directed lugs 156 are dimensioned such that the inner housing 140 is urged to rotate on upward vertical movement of the protrusions 143, as occurs when the pressurised dispensing container 15 is released due to the biasing force of the spring, as well as downward vertical movement, as occurs when the pressurised dispensing container 15 is depressed.

When the pins 162 reach the bottom of the helical groove 141 the device locks-out preventing any further dispensation.

The following variations to the invention may advantageously be incorporated, either singly or in combination, in the apparatus described above.

The inner housing 140 may be dispensed with and the helical groove 141 be provided in the container

- 10 -

wall of the pressurised dispensing container 15 and the protrusions 143 provided on the ferrule of the pressurised dispensing container 15.

5 The ring 160 may be replaced with a series of numbers or other markings spaced around the inner housing 140 or pressurised dispensing container 15 in a helical arrangement and spaced such that only a single number or marking is visible at any one time through the slots 170.

10 The inner housing may be non-rotatable and the collar 155 may be rotatable on interaction with the protrusions 143 of the inner housing 140. A series of markings or numbers are printed around the collar 155 and arranged such that at any one time a single number or marking is visible to a user of the apparatus
15 through, for example, a sight window in the main housing 10.

The inner housing 140 may be non-rotatable and a helical slot be provided in the generally cylindrical
20 portion 11 of the main housing 10 in which the ring 160 is deployed as shown in Figure 13. The ring 160 is operatively connected to the collar 155. Actuation of the apparatus causes the collar 155 and ring 160 to rotate about the inner housing 140 such that the pins
25 161 of the ring 160 move downwardly and around the helical slot.

The ring 160 may be replaced by a marker 200 having protrusions 202, 203 on each side as shown in Figure 14. The inwardly directed protrusion 203 is
30 disposed at an angle to the edges of the marker 200 such that it is received slidingly in the helical groove 141 of the inner housing. The outwardly directed protrusion 202 is disposed parallel to the

- 11 -

edges of the marker 200 such that it is received
slidingly in the vertical slot 170 of the main housing
10 when positioned between the inner housing 140 and
the main housing 10 as shown in Figure 15. An
5 indicating dot 204 may be provided to indicate which
marking 172 is designated.

Similarly to ring 160 relative movement of the
inner housing 140 and the cylindrical portion 11 of
the main housing 10 causes the marker 200 to move
10 along the longitudinal axis of the cylindrical portion
11 in the direction of arrow 205.

The protrusions 143 and the collar 155 may be
provided aligned with the top end of the inner housing
140 remote from the valve stem receiving block 13
15 rather than at the bottom end.

Claims:

1. Dispensing apparatus comprising a housing (10) for receiving a pressurised container (15) containing product for dispensation, a series of markings (172) indicative of quantities of product in the container, indicator means (160; 200) for indicating one of the markings of the series, and means for effecting relative movement between the indicator means and the series of markings on actuation of the pressurised container so as to designate a subsequent marking of the series.
2. Dispensing apparatus as claimed in claim 1 wherein a cylindrical member (140) is located in the housing (10), one of the housing and the cylindrical member being provided with a longitudinal slot (170) and the other of the housing and the cylindrical member having a helical channel (141) along its longitudinal axis, the indicator means (160; 200) being operatively connected to both the longitudinal slot and helical channel such that rotation of the cylindrical member relative to the housing moves the indicator means along the longitudinal axis of the cylindrical member.
3. Dispensing apparatus as claimed in claim 2 wherein the housing (10) and the cylindrical member (140) are provided with co-operating formations (143, 156) having angled abutment surfaces such that relative longitudinal movement between the housing and the cylindrical member causes relative rotation between the housing and cylindrical member.

4. Dispensing apparatus as claimed in claim 1
wherein one of the housing and the pressurised
container (15) is provided with a longitudinal slot
(170) and the other of the housing and the pressurised
5 container is provided with a helical channel (141)
along its longitudinal axis, the indicator means (160;
200) being operatively connected to both the
longitudinal slot and helical channel such that
rotation of the pressurised container relative to the
10 housing moves the indicator means along the
longitudinal axis of the housing.

5. Dispensing apparatus as claimed in claim 4
wherein the housing (10) and the pressurised container
15 (15) are provided with co-operating formations (143,
156) having angled abutment surfaces such that
relative longitudinal movement between the housing and
the pressurised container causes relative rotation
between the housing and pressurised container.

20 6. Dispensing apparatus as claimed in any of claims
2 to 5 wherein the housing (10) comprises a collar
(155) having one of the co-operating formations (143;
156) formed thereon.

25 7. Dispensing apparatus as claimed in any of claims
2 to 6 wherein the indicator means is a ring having
one or more pins located in the longitudinal slot
(170) and the helical channel (141).

30 8. Dispensing apparatus as claimed in any of claims
2 to 6 wherein the indicator means is a marker (200)
having a first protrusion (203) engaged in the helical

channel (141) and a second protrusion (202) located in the longitudinal slot (170).

9. Dispensing apparatus as claimed in claim 1
5 wherein the housing (10) comprises a longitudinal slot (170) and the series of markings (172) are provided in a helical arrangement around the pressurised container (15) or other member (140; 155) located in the housing, such that only one of the series of markings
10 is visible through the slot at any one time.

10. Dispensing apparatus as claimed in any preceding claim comprising means (173) for locking out operation of the pressurised container after a pre-determined
15 number of actuations.

11. Dispensing apparatus as claimed in any preceding claim wherein the housing (10) comprises a mouthpiece (12) which is detachable.
20

12. Dispensing apparatus as claimed in any preceding claim further comprising a pressurised dispensing container (15) located in the housing (10).

FIG. 1.




FIG. 2.




FIG. 3.




FIG. 4.




FIG. 5.




FIG. 6.




FIG. 7.




FIG. 8.




FIG. 9.




FIG. 10.




FIG. 12.




FIG. 11.





FIG. 13.



INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 00/01180

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 B65D83/14 A61M15/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 B65D A61M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EP0-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 349 945 A (WASS ET AL.) 27 September 1994 (1994-09-27) the whole document ---	1, 12
X	W0 98 56444 A (GLAXO) 17 December 1998 (1998-12-17) abstract; figures -----	1, 12

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

28 June 2000

Date of mailing of the international search report

06/07/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Gino, C

INTERNATIONAL SEARCH REPORT

Information on patent family members

Intern. Application No

PCT/GB 00/01180

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5349945 A	27-09-1994	AU 9060491 A	25-06-1992
		DE 69108929 D	18-05-1995
		DE 69108929 T	23-11-1995
		EP 0559757 A	15-09-1993
		WO 9209324 A	11-06-1992
WO 9856444 A	17-12-1998	AU 8213798 A	30-12-1998
		AU 8213898 A	30-12-1998
		AU 8436498 A	30-12-1998
		WO 9856445 A	17-12-1998
		WO 9856446 A	17-12-1998
		EP 0988077 A	29-03-2000
		EP 0988078 A	29-03-2000
		EP 0986412 A	22-03-2000
		HR 980304 A	30-04-1999
		NO 996085 A	09-02-2000